

Package: dtt (via r-universe)

October 17, 2024

Type Package

Title Discrete Trigonometric Transforms

Version 0.1-2

Date 20013-12-30

Author Lukasz Komsta

Maintainer Lukasz Komsta <lukasz.komsta@umlub.pl>

License GPL (>= 2)

URL <http://www.r-project.org>, <http://www.komsta.net/>

Description This package provides functions for 1D and 2D Discrete Cosine Transform (DCT), Discrete Sine Transform (DST) and Discrete Hartley Transform (DHT).

Date/Publication 2013-12-30 11:44:32

NeedsCompilation no

Repository <https://luqqe.r-universe.dev>

RemoteUrl <https://github.com/cran/dtt>

RemoteRef HEAD

RemoteSha d425b271ca19387f1fffc2103907e8aebbc376f

Contents

dtt-package	2
dtt	2
mvdtt	3

Index

5

dtt-package

*Discrete Trigonometric Transforms***Description**

This package provides functions for 1D and 2D Discrete Cosine Transform (DCT), Discrete Sine Transform (DST) and Discrete Hartley Transform (DHT).

Details

Package:	dtt
Type:	Package
Version:	0.1-1
Date:	2007-02-25
License:	GPL version 2 or newer.

Author(s)

Maintainer: Lukasz Komsta <luke@novum.am.lublin.pl>

dtt

*Discrete Trigonometric Transforms***Description**

Performs univariate discrete sine, cosine or Hartley transform.

Usage

```
dtt(x, type = c("dct", "dst", "dht"), variant = 2, inverted = FALSE)
dct(x, variant = 2, inverted = FALSE)
dst(x, variant = 2, inverted = FALSE)
dht(x, inverted = FALSE)
```

Arguments

x	a vector or matrix to be transformed
type	type of transform. Default "dct" is discrete cosine, "dst" is discrete sine and "dht" is discrete Hartley
variant	a transformation variant - 1...4 for DCT-I...DCT-IV or DST-I...DST-IV. Default is DCT-II or DST-II. Ignored when type = "dht"
inverted	if the inverted transform should be performed?

Details

This function transforms a vector of real numbers into a vector of its DCT, DST or DHT components, of the same length.

If the x is a matrix, the transform goes by rows (each row of a result is a transform of corresponding row in x).

The `dct`, `dst` and `dht` functions are simple wrappers for choosing the type by function name.

Value

A transformed vector.

Author(s)

Lukasz Komsta

References

1. N. Ahmed, T. Natarajan, and K. R. Rao, "Discrete Cosine Transform", IEEE Trans. Computers, 90-93, Jan 1974.
2. S. A. Martucci, "Symmetric convolution and the discrete sine and cosine transforms", IEEE Trans. Sig. Processing SP-42, 1038-1051 (1994).
3. R. V. L. Hartley, "A more symmetrical Fourier analysis applied to transmission problems," Proc. IRE 30, 144-150 (1942).

See Also

[mvdtt](#), [fft](#), [mvfft](#)

Examples

```
x=seq(0,20,length=200)
y=x*sin(x)+cos(x)+5*cos(10*x)+rnorm(200, sd=0.1)
plot(y)
z=dct(y); z[151:200]=0; lines(dct(z,inverted=TRUE),col=2);
z=dct(y); z[21:200]=0; lines(dct(z,inverted=TRUE),col=4);
```

Description

Performs multivariate (2D) discrete sine, cosine or Hartley transform.

Usage

```
mvdtt(x, type = c("dct", "dst", "dht"), variant = 2, inverted = FALSE)
mvdct(x, variant = 2, inverted = FALSE)
mvdst(x, variant = 2, inverted = FALSE)
mvdht(x, inverted = FALSE)
```

Arguments

<code>x</code>	a matrix to be transformed
<code>type</code>	type of transform. Default "dct" is discrete cosine, "dst" is discrete sine and "dht" is discrete Hartley
<code>variant</code>	a transformation variant - 1...4 for DCT-I...DCT-IV or DST-I...DST-IV. Default is DCT-II or DST-II. Ignored when type = "dht"
<code>inverted</code>	if the inverted transform should be performed?

Details

This function transforms a matrix of real numbers into a matrix of its DCT, DST or DHT components, of the same dimensions. It is done by so-called row-matrix algorithm.

The `mvdct`, `mvdst` and `mvdht` functions are simple wrappers for choosing the type by function name.

Value

A transformed matrix.

Author(s)

Lukasz Komsta

References

1. N. Ahmed, T. Natarajan, and K. R. Rao, "Discrete Cosine Transform", IEEE Trans. Computers, 90-93, Jan 1974.
2. S. A. Martucci, "Symmetric convolution and the discrete sine and cosine transforms", IEEE Trans. Sig. Processing SP-42, 1038-1051 (1994).
3. R. V. L. Hartley, "A more symmetrical Fourier analysis applied to transmission problems," Proc. IRE 30, 144-150 (1942).

See Also

[dtt](#), [fft](#), [mvfft](#)

Examples

```
x = rnorm(100);
dim(x) = c(10,10);
x
mvdct(x)
mvdct(mvdct(x),inverted=TRUE)
```

Index

- * **models**

- dtt, [2](#)

- mvdtt, [3](#)

- * **package**

- dtt-package, [2](#)

- dct (dtt), [2](#)

- dht (dtt), [2](#)

- dst (dtt), [2](#)

- dtt, [2, 4](#)

- dtt-package, [2](#)

- fft, [3, 4](#)

- mvdct (mvdtt), [3](#)

- mvdht (mvdtt), [3](#)

- mvdst (mvdtt), [3](#)

- mvdtt, [3, 3](#)

- mvfft, [3, 4](#)